

DREAMY

MARBLE LOOK



Experience the breath-taking beauty of this innovative porcelain tile, a perfect fusion of elegance and durability. Enhanced with high-definition detail, creating a visual symphony that elevates any space. This is a stunning combination of classic Marble and Ceppo Stone that is not just a flooring solution, but a work of art that brings sophistication and refinement to any project.

Colours: White, Cream, Grey, Antracite

Thickness: 10mm, 20mm

Sizes: 300x300mm, 300x600mm, 600x600mm, 600x1200mm,
400x600x20mm, 600x600x20mm External Paver

Finishes: Surfasetec In/Out and External

Accessories: Pencil Edge Bullnose 400x600mm (20mm thickness)



WHITE



CREAM



GREY



ANTRACITE



FLOOR: WHITE / SURFACETEC 600x600mm



WALL: WHITE / SURFACETEC 300x600mm



DREAMY
WHITE

FLOOR: WHITE / SURFACETEC 600x1200mm SURFACETEC OUTDOOR EXTERNAL PAVER 600x600mm

DREAMY WHITE



○ FORMATS

300x300mm
300x600mm
600x600mm
600x1200mm

400x600x20mm
Pencil Edge Bullnose
600x600x20mm
External Paver

○ APPLICATIONS

Interior
Exterior
Wall
Floor

Residential
Light Commercial
Pool Areas

○ SURFACES

Surfacetec In/Out
External

○ Thickness

10mm, 20mm

○ Accessories

Pencil Edge Bullnose 400x600mm
(20mm thickness)



600x1200mm 8 random faces

Please note tile patterns are random and may not represent exactly as shown in the photo.



WALL/FLOOR: CREAM SURFACETEC 600x1200mm

DREAMY CREAM



WALL: CREAM SURFACETEC 300x600mm



FLOOR: CREAM SURFACETEC 600x600mm

DREAMY CREAM

○ FORMATS

300x300mm
300x600mm
600x600mm
600x1200mm

400x600x20mm
Pencil Edge Bullnose
600x600x20mm
External Paver

○ APPLICATIONS

Interior
Exterior
Wall
Floor

Residential
Light Commercial
Pool Areas

○ SURFACES

Surfacetec In/Out
External

○ Thickness

10mm, 20mm

○ Accessories

Pencil Edge Bullnose 400x600mm
(20mm thickness)



600x1200mm 8 random faces

Please note tile patterns are random and may not represent exactly as shown in the photo.



DREAMY GREY

○ FORMATS

300x300mm
300x600mm
600x600mm
600x1200mm

400x600x20mm
Pencil Edge Bullnose
600x600x20mm
External Paver

○ APPLICATIONS

Interior
Exterior
Wall
Floor

Residential
Light Commercial
Pool Areas

○ SURFACES

Surfacetec In/Out
External

○ Thickness

10mm, 20mm

○ Accessories

Pencil Edge Bullnose 400x600mm
(20mm thickness)



600x1200mm 8 random faces

Please note tile patterns are random and may not represent exactly as shown in the photo.



FLOOR AND OUTDOOR PAVER: SURFACETEC 600x600mm

DREAMY **ANTRACITE**



WALL/FLOOR: ANTRACITE SURFACETEC 600x1200mm

DREAMY ANTRACITE

○ FORMATS

300x300mm
300x600mm
600x600mm
600x1200mm

400x600x20mm
Pencil Edge Bullnose
600x600x20mm
External Paver

○ APPLICATIONS

Interior
Exterior
Wall
Floor

Residential
Light Commercial
Pool Areas

○ SURFACES

Surfacetec In/Out
External

○ Thickness

10mm, 20mm

○ Accessories

Pencil Edge Bullnose 400x600mm
(20mm thickness)



600x1200mm 8 random faces

Please note tile patterns are random and may not represent exactly as shown in the photo.

Accessories - Pencil Edge bullnose



WHITE
◀ 400x600mm
■ 20mm



CREAM
◀ 400x600mm
■ 20mm



GREY
◀ 400x600mm
■ 20mm



ANTRACITE
◀ 400x600mm
■ 20mm



Pencil Edge Bullnose
400x600mm
■ 20mm

FLOOR: WHITE / EXTERNAL PAVER 600x600x20mm, Pencil Edge Bullnose 400x600x20mm



Pencil Edge Bullnose
400x600mm
E 20mm

FLOOR: GREY / EXTERNAL PAVER 600x600x20mm, Pencil Edge Bullnose 400x600x20mm

TECHNICAL SPECIFICATIONS

TECHNICAL CHARACTERISTIC	STANDARD TEST METHOD	PRESCRIBED VALUES	MANUFACTURER'S VALUES
MEASUREMENT & SURFACE APPEARANCE			
LENGTH	EN ISO 10545-2	±0.6%	±0.1%
WIDTH	EN ISO 10545-2	±0.6%	±0.1%
THICKNESS	EN ISO 10545-2	±5%	±1%
TRANSMUTATION	EN ISO 10545-2	±0.5%	±0.1%
PHYSICAL PROPERTIES			
WATER ABSORPTION	EN ISO 10545-3	≤0.5%	≤0.1%
BREAKING STRENGTH	EN ISO 10545-4	≥1300N	≥1300N
MODULUS OF RUPTURE	EN ISO 10545-4	≥35N/mm ²	≥35N/mm ²
RESISTANCE TO ABRASION	EN ISO 10545-7	—	CLASS 3
SLIP RESISTANCE, WET PENDULUM TEST METHOD, SLIDER 96	AS 4586-2013/AMDT 1-2017 APPENDIX A	N/A	P4
SLIP RESISTANCE, OIL-WET INCLINING PLATFORM TEST METHOD	AS 4586-2013/AMDT 1-2017 APPENDIX D	N/A	R10
CHEMICAL PROPERTIES			
RESISTANCE TO CHEMICALS RESISTANCE TO HOUSEHOLD CHEMICALS AND SWIMMING POOL SALTS	EN ISO 10545-13	MINIMUM GB	PASS
RESISTANCE TO STAINING	EN ISO 10545-14 when subjected to chemicals	MINIMUM CLASS 3	PASS

PACKING SPECIFICATIONS

SERIES	SIZES	PCS / CTN	M ² / CTN	M ² / PLT	CTN / PLT	KG / PLT
DREAMY	600x1200mm	2	1.44	86.4	60	2070
	600x600mm	4	1.44	57.6	40	1240
	300x600mm	8	1.44	57.6	40	1240
	300x300cm	11	0.99	55.44	56	1232
	400x600x20mm	2	0.48	30.72	64	1440
	600x600x20mm	2	0.72	28.8	40	1280

